

Hylomar Exhaust Repair Putty

Description

Hylomar Exhaust Repair Putty is a water based, heat curing repair compound. It has been specifically designed for use in the repair and assembly of exhaust systems for automotive and other general applications. The asbestos free formulation will withstand both pressure and temperatures typically found in vehicle exhaust systems.

Typical Properties

| | |
|--|---|
| Appearance | Viscous Putty |
| Specific Gravity @ 20°C (68°F) (ASTM D4659) | 1.89 |
| Service Temperature | Up to 1000 ⁰ C (1832 ⁰ F) |
| Shelf Life | 12 months minimum |

Directions for use

Ensure the surfaces to be joined are clean and free of loose rust, dirt and grease. Abrade the surface with medium emery paper or wire brush. Moisten the area with water and apply the putty with a knife. Force the putty into the repair to give added strength. Soften putty with water if necessary. Replace lid firmly after use. Run the engine at low speed until warm, this will ensure rapid hardening of the repair putty and will set to form a gas tight seal.

CAUTION: Avoid running engines in confined spaces.

Typical Applications

For use as an exhaust repair compound. When heated the product cures to form a gas tight seal which is both carbon monoxide proof and resistant to vibration.

Any equipment used in the application of Hylomar Exhaust Repair Putty may be cleaned using water or a detergent solution

Handling & Safety

The shelf life of Hylomar Exhaust Repair Putty is a minimum of 12 months when kept in original unopened containers and stored in dry, well ventilated conditions away from strong sun light and frost.

The product is not considered as hazardous under current health & safety regulations if the following precautions are observed.

- Keep out of reach of Children
- In case of contact with eyes, rinse immediately with plenty of clean water and seek medical advice.
- Wear suitable gloves.
- If swallowed seek immediate medical advise and show label or container.

Information given in this publication is based upon technical data gained in our own and other Laboratories and is believed to be true. However the material is used in conditions beyond our control thus we can assume no liability for results obtained or damages incurred through the application of the data present herein.

| | | | |
|--|---------------|--------------------------------------|-------------|
| Hylomar Ltd, Cale Lane, Wigan WN2 1JT UK Tel: +44 (0) 1942 617000 Fax: +44 (0) 1942 617001 | Revision date | 17.09.15 | Page 1 of 2 |
| | Product name | Hylomar Exhaust Repair Putty Issue 2 | |

- After contact with skin, wash contact area with soap and water.

Packaging

Hylomar Exhaust Repair Putty is available in 250g (8.82oz) pots. For full details please contact our Sales Department.

Information given in this publication is based upon technical data gained in our own and other Laboratories and is believed to be true. However the material is used in conditions beyond our control thus we can assume no liability for results obtained or damages incurred through the application of the data present herein.

| | | | |
|--|---------------|--------------------------------------|-------------|
| Hylomar Ltd, Cale Lane, Wigan WN2 1JT UK Tel: +44 (0) 1942 617000 Fax: +44 (0) 1942 617001 | Revision date | 17.09.15 | Page 2 of 2 |
| | Product name | Hylomar Exhaust Repair Putty Issue 2 | |