

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1. Product identifier

Trade name or designation of the mixture	Hylomar ST574 Part B Base
Registration number	-
Synonyms	None.
SDS number	25
Issue date	15-March-2017
Version number	01
Revision date	-
Supersedes date	-

1.2. Relevant identified uses of the substance or mixture and uses advised against

Identified uses	Cable Gland Putty
Uses advised against	None known.

1.3. Details of the supplier of the safety data sheet

Manufacturer:	Hylomar Ltd.
Address:	Hylo House, Cale Lane, New Springs, Wigan, Greater Manchester, UK, WN2 1JT
Telephone number:	+44(0)1942 617000
E-mail address:	info@hylomar.co.uk
Contact person:	Technical Department
1.4. Emergency telephone number	+1-760-476-3961 (US)
	Access code: 333544

SECTION 2: Hazards identification

2.1. Classification of the substance or mixture

The mixture has been assessed and/or tested for its physical, health and environmental hazards and the following classification applies.

Classification according to Regulation (EC) No 1272/2008 as amended

Health hazards

Skin corrosion/irritation	Category 2	H315 - Causes skin irritation.
Serious eye damage/eye irritation	Category 2	H319 - Causes serious eye irritation.
Skin sensitisation	Category 1	H317 - May cause an allergic skin reaction.
Specific target organ toxicity - repeated exposure	Category 1 (lungs)	H372 - Causes damage to organs (lungs) through prolonged or repeated exposure.

Environmental hazards

Hazardous to the aquatic environment, long-term aquatic hazard	Category 2	H411 - Toxic to aquatic life with long lasting effects.
--	------------	---

Hazard summary

Causes damage to organs through prolonged or repeated exposure. Causes serious eye irritation. Causes skin irritation. Exposure to powder or dusts may be irritating to eyes, nose and throat. May cause an allergic skin reaction. Prolonged exposure may cause chronic effects. Dangerous for the environment if discharged into watercourses. Occupational exposure to the substance or mixture may cause adverse health effects.

2.2. Label elements

Label according to Regulation (EC) No. 1272/2008 as amended

Contains:	Epoxy resin mw ≤ 700, Quartz, Talc
-----------	------------------------------------

Hazard pictograms



Signal word

Danger

Hazard statements

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H372 Causes damage to organs (lungs) through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Precautionary statements

Prevention

P260 Do not breathe dust.
P280 Wear protective gloves/protective clothing/eye protection/face protection.

Response

P308 + P313 IF exposed or concerned: Get medical advice/attention.
P305 + P351 + P338 IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
P333 + P313 If skin irritation or rash occurs: Get medical advice/attention.

Storage

Store away from incompatible materials.

Disposal

P501 Dispose of contents/container in accordance with local/regional/national/international regulations.

Supplemental label information None.

2.3. Other hazards Not a PBT or vPvB substance or mixture.

SECTION 3: Composition/information on ingredients

3.2. Mixtures

General information

Chemical name	%	CAS-No. / EC No.	REACH Registration No.	INDEX No.	Notes
Epoxy resin mw ≤ 700	20 - 30	25068-38-6 500-033-5	-	603-074-00-8	
Classification:	Skin Irrit. 2;H315, Skin Sens. 1;H317, Eye Irrit. 2;H319, Aquatic Chronic 2;H411				
Quartz	10 - 20	14808-60-7 238-878-4	-	-	
Classification:	STOT RE 1;H372				
Talc	5 - 10	14807-96-6 238-877-9	-	-	
Classification:	STOT RE 1;H372				

Composition comments All concentrations are in percent by weight unless ingredient is a gas. Gas concentrations are in percent by volume. The full text for all H-statements is displayed in section 16.

SECTION 4: First aid measures

General information

Ensure that medical personnel are aware of the material(s) involved, and take precautions to protect themselves. Wash contaminated clothing before reuse.

4.1. Description of first aid measures

Inhalation

Move to fresh air. Call a physician if symptoms develop or persist.

Skin contact

Remove contaminated clothing immediately and wash skin with soap and water. In case of eczema or other skin disorders: Seek medical attention and take along these instructions. Wash contaminated clothing before reuse.

Eye contact

Immediately flush eyes with plenty of water for at least 15 minutes. Remove contact lenses, if present and easy to do. Continue rinsing. Get medical attention if irritation develops and persists.

Ingestion

Rinse mouth. Get medical attention if symptoms occur.

4.2. Most important symptoms and effects, both acute and delayed

Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash. Prolonged exposure may cause chronic effects.

4.3. Indication of any immediate medical attention and special treatment needed

Provide general supportive measures and treat symptomatically. Keep victim under observation. Symptoms may be delayed.

SECTION 5: Firefighting measures

General fire hazards

No unusual fire or explosion hazards noted.

5.1. Extinguishing media

Suitable extinguishing media Water fog. Foam. Dry chemical powder. Carbon dioxide (CO₂).

Unsuitable extinguishing media Do not use water jet as an extinguisher, as this will spread the fire.

5.2. Special hazards arising from the substance or mixture

During fire, gases hazardous to health may be formed.

5.3. Advice for firefighters

Special protective equipment for firefighters Self-contained breathing apparatus and full protective clothing must be worn in case of fire.

Special fire fighting procedures Move containers from fire area if you can do so without risk.

Specific methods

Use standard firefighting procedures and consider the hazards of other involved materials.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

For non-emergency personnel Avoid contact with skin and eyes. Avoid breathing dust. Do not touch damaged containers or spilled material unless wearing appropriate protective clothing.

For emergency responders Keep unnecessary personnel away. Wear appropriate protective equipment and clothing during clean-up.

6.2. Environmental precautions

Prevent further leakage or spillage if safe to do so. Do not discharge into drains, water courses or onto the ground.

6.3. Methods and material for containment and cleaning up

Ventilate the area.

Large Spills: Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible. Absorb spill with vermiculite or other inert material, then place in a container for chemical waste for proper disposal. Following product recovery, flush area with water.

Small Spills: Wipe up with absorbent material (e.g. cloth, fleece). Clean surface thoroughly to remove residual contamination.

Never return spills in original containers for re-use.

6.4. Reference to other sections

For personal protection, see section 8 of the SDS. For waste disposal, see section 13 of the SDS.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Do not breathe dust. Avoid contact with eyes, skin, and clothing. Persons with epoxy allergy should not work with this product. Use Personal Protective Equipment recommended in section 8 of the SDS. Wash thoroughly after handling. Observe good industrial hygiene practices. Avoid release to the environment.

7.2. Conditions for safe storage, including any incompatibilities

Keep containers tightly closed in a dry, cool and well-ventilated place. Store away from incompatible materials.

7.3. Specific end use(s)

Cable Gland Putty

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Occupational exposure limits

UK. EH40 Workplace Exposure Limits (WELs)

Components	Type	Value	Form
Calcium carbonate, synthetic (CAS 471-34-1)	TWA	4 mg/m ³	Respirable dust.
		4 mg/m ³	Respirable.
		10 mg/m ³	Inhalable
		10 mg/m ³	Inhalable dust.
Quartz (CAS 14808-60-7)	TWA	0.1 mg/m ³	Respirable.
Talc (CAS 14807-96-6)	TWA	1 mg/m ³	Respirable dust.

Biological limit values

No biological exposure limits noted for the ingredient(s).

Recommended monitoring procedures

Follow standard monitoring procedures.

Derived no effect levels (DNELs)

Not available.

Predicted no effect concentrations (PNECs)	Not available.
8.2. Exposure controls	
Appropriate engineering controls	Provide adequate ventilation. Observe occupational exposure limits and minimise the risk of exposure. Provide easy access to water supply and eye wash facilities.
Individual protection measures, such as personal protective equipment	
General information	Personal protective equipment should be chosen according to the CEN standards and in discussion with the supplier of the personal protective equipment.
Eye/face protection	Wear approved safety glasses or goggles.
Skin protection	
- Hand protection	Wear protective gloves. Nitrile or neoprene gloves are recommended. Suitable gloves can be recommended by the glove supplier.
- Other	Normal work clothing (long sleeved shirts and long pants) is recommended.
Respiratory protection	If engineering controls do not maintain airborne concentrations below recommended exposure limits (where applicable) or to an acceptable level (in countries where exposure limits have not been established), an approved respirator must be worn. Use respiratory equipment with combination filter, type A2/P2.
Thermal hazards	Wear appropriate thermal protective clothing, when necessary.
Hygiene measures	Always observe good personal hygiene measures, such as washing after handling the material and before eating, drinking, and/or smoking. Routinely wash work clothing and protective equipment to remove contaminants.
Environmental exposure controls	Environmental manager must be informed of all major releases.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Appearance

Physical state	Solid.
Form	Putty.
Colour	Dark red.
Odour	Low resinous odour.
Odour threshold	Not available.
pH	Not applicable.
Melting point/freezing point	Not available.
Initial boiling point and boiling range	Not available.
Flash point	Not applicable.
Evaporation rate	Not applicable.
Flammability (solid, gas)	Not available.

Upper/lower flammability or explosive limits

Flammability limit - lower (%)	Not available.
Flammability limit - upper (%)	Not available.
Vapour pressure	Not applicable.
Vapour density	Not applicable.
Relative density	2 (20 °C)
Solubility(ies)	Insoluble in water.
Partition coefficient (n-octanol/water)	No data available.
Auto-ignition temperature	Not available.
Decomposition temperature	Not available.
Viscosity	Not applicable.
Explosive properties	Not explosive.
Oxidising properties	Not oxidising.
9.2. Other information	No relevant additional information available.

SECTION 10: Stability and reactivity

10.1. Reactivity	The product is stable and non reactive under normal conditions of use, storage and transport.
10.2. Chemical stability	Material is stable under normal conditions.
10.3. Possibility of hazardous reactions	No dangerous reaction known under conditions of normal use.
10.4. Conditions to avoid	Contact with incompatible materials.
10.5. Incompatible materials	Acids. Strong oxidising agents. Strong bases. Amines.
10.6. Hazardous decomposition products	Thermal decomposition or combustion may liberate carbon oxides and other toxic gases or vapours. Silicon oxides.

SECTION 11: Toxicological information

General information Occupational exposure to the substance or mixture may cause adverse effects.

Information on likely routes of exposure

Inhalation	May cause damage to organs through prolonged or repeated exposure by inhalation. Dust may irritate respiratory system.
Skin contact	Causes skin irritation. May cause an allergic skin reaction.
Eye contact	Causes serious eye irritation.
Ingestion	May cause discomfort if swallowed. However, ingestion is not likely to be a primary route of occupational exposure.

Symptoms Severe eye irritation. Symptoms may include stinging, tearing, redness, swelling, and blurred vision. Dusts may irritate the respiratory tract, skin and eyes. Coughing. Skin irritation. May cause redness and pain. May cause an allergic skin reaction. Dermatitis. Rash.

11.1. Information on toxicological effects

Acute toxicity Not expected to be acutely toxic.

Components	Species	Test results
Talc (CAS 14807-96-6)		
Acute Oral		
LD50	Rat	> 5000 mg/kg
Skin corrosion/irritation	Causes skin irritation.	
Serious eye damage/eye irritation	Causes serious eye irritation.	
Respiratory sensitisation	Based on available data, the classification criteria are not met.	
Skin sensitisation	May cause an allergic skin reaction.	
Germ cell mutagenicity	Based on available data, the classification criteria are not met.	
Carcinogenicity	Based on available data, the classification criteria are not met.	
IARC Monographs. Overall Evaluation of Carcinogenicity		
Quartz (CAS 14808-60-7)		1 Carcinogenic to humans.
Talc (CAS 14807-96-6)		2B Possibly carcinogenic to humans. 3 Not classifiable as to carcinogenicity to humans.
Reproductive toxicity	Based on available data, the classification criteria are not met.	
Specific target organ toxicity - single exposure	Based on available data, the classification criteria are not met.	
Specific target organ toxicity - repeated exposure	Causes damage to organs (lungs) through prolonged or repeated exposure.	
Aspiration hazard	Due to the physical form of the product it is not expected to be an aspiration hazard.	
Mixture versus substance information	No information available.	
Other information	Symptoms may be delayed.	

SECTION 12: Ecological information

12.1. Toxicity Toxic to aquatic life with long lasting effects.

Components	Species	Test results
Epoxy resin mw ≤ 700 (CAS 25068-38-6)		
Aquatic		
Crustacea	EC50 Daphnia magna	2.7 mg/l, 48 hours

Components	Species	Test results
Fish	LC50 Oncorhynchus mykiss	1.2 mg/l, 96 hours
12.2. Persistence and degradability	No data available.	
12.3. Bioaccumulative potential	The product is not expected to bioaccumulate.	
Partition coefficient n-octanol/water (log Kow)	No data available.	
Bioconcentration factor (BCF)	Not available.	
12.4. Mobility in soil	The product is insoluble in water. Expected to have low mobility in soil.	
12.5. Results of PBT and vPvB assessment	Not a PBT or vPvB substance or mixture.	
12.6. Other adverse effects	No other adverse environmental effects (e.g. ozone depletion, photochemical ozone creation potential, endocrine disruption, global warming potential) are expected from this component.	

SECTION 13: Disposal considerations

13.1. Waste treatment methods

Residual waste	Dispose of in accordance with local regulations. Empty containers or liners may retain some product residues. This material and its container must be disposed of in a safe manner (see: Disposal instructions).
Contaminated packaging	Empty containers should be taken to an approved waste handling site for recycling or disposal.
EU waste code	08 04 09* The Waste code should be assigned in discussion between the user, the producer and the waste disposal company.
Disposal methods/information	Do not discharge into drains, water courses or onto the ground. Collect and reclaim or dispose in sealed containers at licensed waste disposal site. Dispose of contents/container in accordance with local/regional/national/international regulations.

SECTION 14: Transport information

ADR

14.1. UN number	UN3077
14.2. UN proper shipping name	Environmentally hazardous substance, solid, n.o.s. (Epoxy resin mw ≤ 700)
14.3. Transport hazard class(es)	
Class	9
Subsidiary risk	-
Label(s)	9
Hazard No. (ADR)	90
Tunnel restriction code	E
14.4. Packing group	III
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

RID

14.1. UN number	UN3077
14.2. UN proper shipping name	Environmentally hazardous substance, solid, n.o.s. (Epoxy resin mw ≤ 700)
14.3. Transport hazard class(es)	
Class	9
Subsidiary risk	-
Label(s)	9
14.4. Packing group	III
14.5. Environmental hazards	No.
14.6. Special precautions for user	Read safety instructions, SDS and emergency procedures before handling.

ADN

14.1. UN number	UN3077
14.2. UN proper shipping name	Environmentally Hazardous Solid, N.o.s. (Epoxy resin mw ≤ 700)
14.3. Transport hazard class(es)	
Class	9
Subsidiary risk	-
Label(s)	9
14.4. Packing group	III

- 14.5. Environmental hazards** No.
14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IATA

- 14.1. UN number** UN3077
14.2. UN proper shipping name Environmentally hazardous substance, solid, n.o.s. (Epoxy resin mw ≤ 700)
14.3. Transport hazard class(es)
 Class 9
 Subsidiary risk -
 Label(s) 9
14.4. Packing group III
14.5. Environmental hazards No.
ERG Code 9L
14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

IMDG

- 14.1. UN number** UN3077
14.2. UN proper shipping name ENVIRONMENTALLY HAZARDOUS SUBSTANCE, SOLID, N.O.S. (Epoxy resin mw ≤ 700)
14.3. Transport hazard class(es)
 Class 9
 Subsidiary risk -
14.4. Packing group III
14.5. Environmental hazards
 Marine pollutant No.
 EmS F-A, S-F
14.6. Special precautions for user Read safety instructions, SDS and emergency procedures before handling.

- 14.7. Transport in bulk according to Annex II of Marpol and the IBC Code** Not applicable.

SECTION 15: Regulatory information

15.1. Safety, health and environmental regulations/legislation specific for the substance or mixture

EU regulations

- Regulation (EC) No. 1005/2009 on substances that deplete the ozone layer, Annex I and II, as amended**
Not listed.
Regulation (EC) No. 850/2004 On persistent organic pollutants, Annex I as amended
Not listed.
Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 1 as amended
Not listed.
Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 2 as amended
Not listed.
Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex I, Part 3 as amended
Not listed.
Regulation (EU) No. 649/2012 concerning the export and import of dangerous chemicals, Annex V as amended
Not listed.
Regulation (EC) No. 166/2006 Annex II Pollutant Release and Transfer Registry, as amended
Not listed.
Regulation (EC) No. 1907/2006, REACH Article 59(10) Candidate List as currently published by ECHA
Not listed.

Authorisations

- Regulation (EC) No. 1907/2006, REACH Annex XIV Substances subject to authorisation, as amended**
Not listed.

Restrictions on use

- Regulation (EC) No. 1907/2006, REACH Annex XVII Substances subject to restriction on marketing and use as amended**
Not listed.
Directive 2004/37/EC: on the protection of workers from the risks related to exposure to carcinogens and mutagens at work, as amended.
Not listed.

Other EU regulations

Directive 2012/18/EU on major accident hazards involving dangerous substances, as amended

Epoxy resin mw ≤ 700 (CAS 25068-38-6)

Other regulations

This Safety Data Sheet complies with the requirements of Regulation (EC) No 1907/2006 as amended. The product is classified and labelled in accordance with Regulation (EC) 1272/2008 (CLP Regulation) as amended and respective national laws implementing EC directives.

National regulations

Young people under 18 years old are not allowed to work with this product according to the EU Directive 94/33/EC on the protection of young people at work. Follow national regulation for work with chemical agents.

15.2. Chemical safety assessment

No Chemical Safety Assessment has been carried out.

SECTION 16: Other information

List of abbreviations

PBT: Persistent, bioaccumulative and toxic.
TWA: Time weighted average.
vPvB: Very Persistent and very Bioaccumulative.

References

HSDB® - Hazardous Substances Data Bank
Registry of Toxic Effects of Chemical Substances (RTECS)
ESIS (European chemical Substances Information System)

Information on evaluation method leading to the classification of mixture

The mixture is classified based on test data for physical hazards. The classification for health and environmental hazards is derived by a combination of calculation methods and test data, if available. For details, refer to Sections 9, 11 and 12.

Full text of any H-statements not written out in full under Sections 2 to 15

H315 Causes skin irritation.
H317 May cause an allergic skin reaction.
H319 Causes serious eye irritation.
H372 Causes damage to organs through prolonged or repeated exposure.
H411 Toxic to aquatic life with long lasting effects.

Training information

Follow training instructions when handling this material.

Disclaimer

The information in the sheet was written based on the best knowledge and experience currently available.